



Delta3D Version 2.4.0

dtGUI::

Reference Manual

Contents

1	Main Page	1
2	Todo List	3
3	Directory Documentation	5
3.1	src/dtGUI/ Directory Reference	5
3.2	inc/dtGUI/ Directory Reference	6
3.3	inc/ Directory Reference	7
3.4	src/ Directory Reference	8
4	Namespace Documentation	9
4.1	dtCore Namespace Reference	9
4.1.1	Detailed Description	9
4.2	dtGUI Namespace Reference	10
4.2.1	Detailed Description	10
4.2.2	Typedef Documentation	11
4.2.2.1	Widget	11
4.2.3	Function Documentation	11
4.2.3.1	IMPLEMENT_ENUM	11
5	Class Documentation	13
5.1	BaseScriptModule Class Reference	13
5.1.1	Detailed Description	13
5.1.2	Constructor & Destructor Documentation	13
5.1.2.1	BaseScriptModule	13
5.1.2.2	~BaseScriptModule	13
5.1.3	Member Function Documentation	13
5.1.3.1	executeScriptedEventHandler	13
5.1.3.2	executeScriptFile	14
5.1.3.3	executeScriptGlobal	14
5.1.3.4	executeString	14
5.2	CEGUIConnectionManager Class Reference	15
5.2.1	Detailed Description	15
5.2.2	Constructor & Destructor Documentation	16
5.2.2.1	CEGUIConnectionManager	16
5.2.2.2	~CEGUIConnectionManager	16
5.2.3	Member Function Documentation	16
5.2.3.1	Connect	16

5.2.3.2	Connect	16
5.2.3.3	Disconnect	16
5.2.3.4	Disconnect	16
5.3	CEGUIKeyboardListener Class Reference	17
5.3.1	Constructor & Destructor Documentation	17
5.3.1.1	CEGUIKeyboardListener	17
5.3.1.2	~CEGUIKeyboardListener	17
5.3.2	Member Function Documentation	17
5.3.2.1	HandleKeyPressed	17
5.3.2.2	HandleKeyReleased	17
5.3.2.3	HandleKeyTyped	17
5.3.2.4	KeyboardKeyToKeyScan	17
5.4	CEGUIMemberSignature< T > Class Template Reference	18
5.4.1	Detailed Description	19
5.4.2	Member Typedef Documentation	19
5.4.2.1	CALLBACK_FPTR	19
5.4.3	Constructor & Destructor Documentation	19
5.4.3.1	CEGUIMemberSignature	19
5.4.4	Member Function Documentation	19
5.4.4.1	GetFunctionPtr	19
5.4.4.2	GetObjectPtr	19
5.4.4.3	match	19
5.4.4.4	operator==	19
5.5	CEGUIMemberSignatureBase Class Reference	20
5.5.1	Detailed Description	21
5.5.2	Constructor & Destructor Documentation	21
5.5.2.1	CEGUIMemberSignatureBase	21
5.5.2.2	~CEGUIMemberSignatureBase	21
5.5.3	Member Function Documentation	21
5.5.3.1	GetEventName	21
5.5.3.2	GetEventSet	21
5.5.3.3	operator==	21
5.5.4	Friends And Related Function Documentation	21
5.5.4.1	CEGUIConnectionManager	21
5.5.5	Member Data Documentation	21
5.5.5.1	m_pEventSet	21
5.5.5.2	m_sEventName	21
5.6	CEGUIMouseListener Class Reference	22
5.6.1	Detailed Description	22
5.6.2	Constructor & Destructor Documentation	22
5.6.2.1	CEGUIMouseListener	22

5.6.2.2	~CEGUIMouseListener	22
5.6.3	Member Function Documentation	22
5.6.3.1	HandleButtonClicked	22
5.6.3.2	HandleButtonPressed	22
5.6.3.3	HandleButtonReleased	22
5.6.3.4	HandleMouseDragged	23
5.6.3.5	HandleMouseMove	23
5.6.3.6	HandleMouseScrolled	23
5.6.3.7	SetWindowSize	23
5.7	CEGUIRenderer Class Reference	24
5.7.1	Constructor & Destructor Documentation	25
5.7.1.1	CEGUIRenderer	25
5.7.1.2	CEGUIRenderer	25
5.7.1.3	~CEGUIRenderer	25
5.7.2	Member Function Documentation	25
5.7.2.1	addQuad	25
5.7.2.2	clearRenderList	25
5.7.2.3	createTexture	25
5.7.2.4	createTexture	25
5.7.2.5	createTexture	25
5.7.2.6	destroyAllTextures	25
5.7.2.7	destroyTexture	25
5.7.2.8	doRender	25
5.7.2.9	getDefaultImageCodecName	25
5.7.2.10	getHeight	25
5.7.2.11	getHorzScreenDPI	25
5.7.2.12	getImageCodec	25
5.7.2.13	getMaxTextureSize	25
5.7.2.14	getRect	25
5.7.2.15	getSize	25
5.7.2.16	getVertScreenDPI	25
5.7.2.17	getWidth	25
5.7.2.18	isQueueingEnabled	25
5.7.2.19	setDefaultImageCodecName	25
5.7.2.20	setDisplaySize	25
5.7.2.21	SetGraphicsContext	25
5.7.2.22	setImageCodec	25
5.7.2.23	setImageCodec	25
5.7.2.24	setQueueingEnabled	25
5.8	CEGUISignatureStatic Class Reference	26
5.8.1	Detailed Description	26

5.8.2	Member Typedef Documentation	27
5.8.2.1	CALLBACK_FPTR	27
5.8.3	Constructor & Destructor Documentation	27
5.8.3.1	CEGUISignatureStatic	27
5.8.4	Member Function Documentation	27
5.8.4.1	GetEventName	27
5.8.4.2	GetEventSet	27
5.8.4.3	GetFunctionPtr	27
5.8.4.4	match	27
5.8.4.5	operator==	27
5.9	CEGUITexture Class Reference	28
5.9.1	Detailed Description	28
5.9.2	Constructor & Destructor Documentation	28
5.9.2.1	CEGUITexture	28
5.9.2.2	~CEGUITexture	28
5.9.3	Member Function Documentation	28
5.9.3.1	getHeight	28
5.9.3.2	getOriginalHeight	28
5.9.3.3	getOriginalWidth	29
5.9.3.4	GetOSGTexture	29
5.9.3.5	GetOSGTexture	29
5.9.3.6	GetTextureID	29
5.9.3.7	getWidth	29
5.9.3.8	getXScale	29
5.9.3.9	getYScale	29
5.9.3.10	IsFlippedHorizontal	29
5.9.3.11	loadFromFile	29
5.9.3.12	loadFromMemory	29
5.9.3.13	ResizeToMinPOT	29
5.9.3.14	SetFlipHorizontal	29
5.9.3.15	SetOSGTexture	29
5.10	CEUIDrawable Class Reference	30
5.10.1	Detailed Description	32
5.10.2	Constructor & Destructor Documentation	32
5.10.2.1	CEUIDrawable	32
5.10.2.2	~CEUIDrawable	32
5.10.3	Member Function Documentation	32
5.10.3.1	AddChild	32
5.10.3.2	DisplayProperties	32
5.10.3.3	GetAutoResizing	32
5.10.3.4	GetKeyboardListener	32

5.10.3.5	GetMouseListener	32
5.10.3.6	GetOSGNode	32
5.10.3.7	GetOSGNode	32
5.10.3.8	GetProjectionNode	32
5.10.3.9	GetRenderer	33
5.10.3.10	GetRenderer	33
5.10.3.11	GetTransformNode	33
5.10.3.12	GetUI	33
5.10.3.13	OnMessage	33
5.10.3.14	SetAutoResizing	33
5.10.3.15	SetOSGNode	33
5.10.3.16	SetRenderBinDetails	33
5.10.3.17	SetRenderingSize	33
5.10.3.18	ShutdownGUI	33
5.10.4	Member Data Documentation	33
5.10.4.1	mGeode	33
5.10.4.2	mHeight	33
5.10.4.3	mKeyboard	33
5.10.4.4	mMouse	33
5.10.4.5	mNode	33
5.10.4.6	mProjection	33
5.10.4.7	mRenderer	33
5.10.4.8	mScriptModule	34
5.10.4.9	mTransform	34
5.10.4.10	mUI	34
5.10.4.11	mWidth	34
5.10.4.12	mWindow	34
5.11	ExceptionEnum Class Reference	35
5.11.1	Constructor & Destructor Documentation	35
5.11.1.1	ExceptionEnum	35
5.11.2	Member Data Documentation	35
5.11.2.1	GenericCEGUIException	35
5.12	HUD Class Reference	36
5.12.1	Detailed Description	38
5.12.2	Constructor & Destructor Documentation	39
5.12.2.1	HUD	39
5.12.2.2	HUD	39
5.12.2.3	~HUD	39
5.12.3	Member Function Documentation	39
5.12.3.1	Connect	39
5.12.3.2	Connect	39

5.12.3.3	CreateFont	39
5.12.3.4	CreateWidget	39
5.12.3.5	CreateWidget	39
5.12.3.6	DestroyAllFonts	39
5.12.3.7	DestroyFont	39
5.12.3.8	Disconnect	40
5.12.3.9	Disconnect	40
5.12.3.10	Disconnect	40
5.12.3.11	Disconnect	40
5.12.3.12	Disconnect	40
5.12.3.13	GetFilePath	40
5.12.3.14	GetInternalGraph	40
5.12.3.15	GetIsMouseCursorVisible	40
5.12.3.16	GetKeyboard	40
5.12.3.17	GetKeyboard	40
5.12.3.18	GetMouse	40
5.12.3.19	GetMouse	40
5.12.3.20	GetOrCreateOSGTexture	40
5.12.3.21	GetPrefix	40
5.12.3.22	GetRootsheet	40
5.12.3.23	GetRootSheet	40
5.12.3.24	GetWidget	40
5.12.3.25	LoadLayout	40
5.12.3.26	LoadLayout	41
5.12.3.27	LoadScheme	41
5.12.3.28	MakeCurrent	41
5.12.3.29	SetCamera	41
5.12.3.30	SetFilePath	41
5.12.3.31	SetIsMouseCursorVisible	41
5.12.3.32	SetKeyboard	41
5.12.3.33	SetMouse	41
5.12.3.34	SetMouseCursor	41
5.12.3.35	UnloadAllSchemes	41
5.12.3.36	UnloadScheme	41
5.13	Renderer Class Reference	42
5.13.1	Detailed Description	42
5.13.2	Constructor & Destructor Documentation	42
5.13.2.1	Renderer	42
5.13.2.2	~Renderer	42
5.13.3	Member Function Documentation	42
5.13.3.1	createResourceProvider	42

5.14	ResourceProvider Class Reference	43
5.14.1	Detailed Description	43
5.14.2	Constructor & Destructor Documentation	43
5.14.2.1	ResourceProvider	43
5.14.2.2	~ResourceProvider	43
5.14.3	Member Function Documentation	43
5.14.3.1	loadRawDataContainer	43
5.15	ScriptModule Class Reference	44
5.15.1	Detailed Description	45
5.15.2	Member Typedef Documentation	45
5.15.2.1	CallbackRegistry	45
5.15.2.2	HandlerFunctor	45
5.15.2.3	STATIC_FUNCTION	45
5.15.3	Constructor & Destructor Documentation	45
5.15.3.1	ScriptModule	45
5.15.3.2	~ScriptModule	45
5.15.4	Member Function Documentation	45
5.15.4.1	AddCallback	45
5.15.4.2	AddCallback	46
5.15.4.3	executeScriptedEventHandler	46
5.15.4.4	executeScriptFile	46
5.15.4.5	executeScriptGlobal	46
5.15.4.6	executeString	46
5.15.4.7	GetRegistry	46
6	File Documentation	47
6.1	basescriptmodule.h File Reference	47
6.2	ceguiconnectionmanager.cpp File Reference	48
6.3	ceguiconnectionmanager.h File Reference	49
6.4	ceguiconnectionsignatures.h File Reference	50
6.5	ceguikeyboardlistener.cpp File Reference	51
6.6	ceguikeyboardlistener.h File Reference	52
6.7	ceguimouselistener.cpp File Reference	53
6.8	ceguimouselistener.h File Reference	54
6.9	ceguirenderer.cpp File Reference	55
6.9.1	Define Documentation	55
6.9.1.1	S_	55
6.9.1.2	STRINGIZE	55
6.10	ceguirenderer.h File Reference	56
6.10.1	Define Documentation	56
6.10.1.1	OGLRENDERER_VBUFF_CAPACITY	56

6.11	cegitexture.cpp File Reference	57
6.12	cegitexture.h File Reference	58
6.13	ceuidrawable.cpp File Reference	59
6.14	ceuidrawable.h File Reference	60
6.15	dtgui.h File Reference	61
6.16	export.h File Reference	62
	6.16.1 Define Documentation	62
	6.16.1.1 DT_GUI_EXPORT	62
6.17	guiexceptionenum.cpp File Reference	63
6.18	guiexceptionenum.h File Reference	64
6.19	hud.cpp File Reference	65
	6.19.1 Function Documentation	65
	6.19.1.1 GetCEGUIPrefix	65
6.20	hud.h File Reference	66
6.21	mainpage.h File Reference	67
	6.21.1 Detailed Description	67
6.22	renderer.cpp File Reference	68
6.23	renderer.h File Reference	69
6.24	resourceprovider.cpp File Reference	70
6.25	resourceprovider.h File Reference	71
6.26	scriptmodule.cpp File Reference	72
6.27	scriptmodule.h File Reference	73
6.28	widget.h File Reference	74

Main Page

Delta3D is an Open Source engine which can be used for games, simulations, or other graphical applications.

The **Delta3D** framework exists as a number of modules, each sitting in its own library, enclosed within its own namespace. At the very core lies the **dtCore** library. This contains basic, low-level functionality which is mostly required for all 3D applications written in C++.

Around and alongside this sit other supporting libraries, such as dtUtil (containing reusable features which are useful for most applications), dtTerrain (for rendering terrain databases), dtGame, dtNet, etc.

Extensive online documentation is available from the Delta3D **Docs** section to help in using Delta3D.

The project's original reference guides generated by Doxygen from the source code may be viewed at the Delta3D **API Documentation** section.

To download source code, binaries, dependencies and sample datasets visit the Delta3D **Downloads** page.

For more about dependencies see the Delta3D **Dependencies** page.


The documentation you are looking at can be downloaded from www.3draum.ch.

Enjoy!

Todo List

Directory Documentation


3.1 src/dtGUI/ Directory Reference



Files

- file [ceguiconnectionmanager.cpp](#)
- file [ceguikeyboardlistener.cpp](#)
- file [ceguimouselistener.cpp](#)
- file [ceguirenderer.cpp](#)
- file [ceguitexture.cpp](#)
- file [ceuidrawable.cpp](#)
- file [guiexceptionenum.cpp](#)
- file [hud.cpp](#)
- file [renderer.cpp](#)
- file [resourceprovider.cpp](#)
- file [scriptmodule.cpp](#)

3.2 inc/dtGUI/ Directory Reference



Files

- file [basescriptmodule.h](#)
- file [ceguiconnectionmanager.h](#)
- file [ceguiconnectionsignatures.h](#)
- file [ceguikeyboardlistener.h](#)
- file [ceguimouselistener.h](#)
- file [ceguirenderer.h](#)
- file [ceguitexture.h](#)
- file [ceuidrawable.h](#)
- file [dtgui.h](#)
- file [export.h](#)
- file [guiexceptionenum.h](#)
- file [hud.h](#)
- file [mainpage.h](#)
- file [renderer.h](#)
- file [resourceprovider.h](#)
- file [scriptmodule.h](#)
- file [widget.h](#)


3.3 inc/ Directory Reference



Directories

- directory [dtGUI](#)

3.4 src/ Directory Reference



Directories

- directory [dtGUI](#)

Namespace Documentation

4.1 dtCore Namespace Reference

4.1.1 Detailed Description

4.2 dtGUI Namespace Reference

The `dtGUI` namespace contains the functionality to render and control OpenGL graphical user interfaces.

Classes

- class [BaseScriptModule](#)
An abstract interface for classes used by [CEUIDrawable](#).
- class [CEGUIConnectionManager](#)
this class is used to keep track of connections (event-callbacks) for any widget/EventSet created for/by a gui-object.
- class [CEGUIKeyboardListener](#)
- class [CEGUIMemberSignature](#)
objects instantiated from this class describes an object-member-"signature"
- class [CEGUIMemberSignatureBase](#)
Common interface for a member-callback-connection-signatures.
- class [CEGUIMouseListener](#)
A mouse device listener to inject input to CEGUI.
- class [CEGUIRenderer](#)
- class [CEGUISignatureStatic](#)
objects instantiated from this class describes a static-method's signature
- class [CEGUITexture](#)
implementation of the `CEGUI::Texture` for `OpenSceneGraph`
- class [CEUIDrawable](#)
A `DeltaDrawable` used to render CEGUI.
- class [ExceptionEnum](#)
- class [HUD](#)
gui-class for rendering and managing widgets
- class [Renderer](#)
Simple CEGUI rendering class based on the `CEGUI::OpenGLRender` class.
- class [ResourceProvider](#)
A simple CEGUI [ResourceProvider](#) based on the `CEGUI::DefaultResourceProvider`.
- class [ScriptModule](#)
[ScriptModule](#) is the binding from `CEGUI::Events` to specific application callbacks.

Typedefs

- typedef `CEGUI::Window` [Widget](#)

Functions

- [IMPLEMENT_ENUM](#) ([ExceptionEnum](#))

4.2.1 Detailed Description

The `dtGUI` namespace contains the functionality to render and control OpenGL graphical user interfaces. `dtGUI` uses `CEGUI` for high-level control of the widgets.

4.2.2 Typedef Documentation

4.2.2.1 typedef CEGUI::Window Widget

4.2.3 Function Documentation


4.2.3.1 dtGUI::IMPLEMENT_ENUM (ExceptionEnum)

Class Documentation

5.1 BaseScriptModule Class Reference

An abstract interface for classes used by [CEUIDrawable](#).

`#include <inc/dtGUI/basescriptmodule.h>`Inheritance diagram for BaseScriptModule:



Public Member Functions

- [BaseScriptModule](#) ()
- virtual [~BaseScriptModule](#) ()
- virtual bool [executeScriptedEventHandler](#) (const CEGUI::String &handlerName, const CEGUI::EventArgs &ea)=0
Overload this function to handle Events triggered from a CEGUI::Window.
- virtual void [executeScriptFile](#) (const CEGUI::String &filename, const CEGUI::String &resourceGroup="")=0
- virtual int [executeScriptGlobal](#) (const CEGUI::String &function_name)=0
- virtual void [executeString](#) (const CEGUI::String &str)=0

5.1.1 Detailed Description

An abstract interface for classes used by [CEUIDrawable](#). [BaseScriptModule](#) is mean to be implemented to provide support for Events triggered by the CEGUI Windows in a GUI scene. See also [dtGUI::ScriptModule](#).

5.1.2 Constructor & Destructor Documentation

5.1.2.1 [BaseScriptModule](#) () [inline]

5.1.2.2 virtual [~BaseScriptModule](#) () [inline, virtual]

5.1.3 Member Function Documentation

5.1.3.1 virtual bool [executeScriptedEventHandler](#) (const CEGUI::String & *handlerName*, const CEGUI::EventArgs & *ea*) [pure virtual]

Overload this function to handle Events triggered from a CEGUI::Window. Parameters

handlerName the name of something to handle this event, typically a function name.

ea the CEGUI::EventArgs that can contain useful information about the CEGUI::Event that occurred.

Implemented in [ScriptModule](#).

5.1.3.2 virtual void executeScriptFile (const CEGUI::String & filename, const CEGUI::String & resourceGroup = "") [pure virtual]

Implemented in [ScriptModule](#).

5.1.3.3 virtual int executeScriptGlobal (const CEGUI::String & function_name) [pure virtual]

Implemented in [ScriptModule](#).

5.1.3.4 virtual void executeString (const CEGUI::String & str) [pure virtual]

Implemented in [ScriptModule](#).


The documentation for this class was generated from the following file:

- [basescriptmodule.h](#)


5.2 CEGUIConnectionManager Class Reference

this class is used to keep track of connections (event-callbacks) for any widget/EventSet created for/by a gui-object.

#include <inc/dtGUI/ceguiconnectionmanager.h> Inheritance diagram for CEGUIConnectionManager:



Collaboration diagram for CEGUIConnectionManager:



Public Member Functions

- void **Connect** (CEGUI::EventSet *pEventSet, const std::string &sEventName, bool(*pFunction)(const CEGUI::EventArgs &))
connects static function to an event
- template<class T >
void **Connect** (CEGUI::EventSet *pEventSet, const std::string &sEventName, bool(T::*pObjectMember)(const CEGUI::EventArgs &), T *pObject)
connects object-member from an event
- void **Disconnect** (CEGUI::EventSet *pEventSet, const std::string &sEventName, bool(*pFunction)(const CEGUI::EventArgs &))
disconnects static functions from an event
- template<class T >
void **Disconnect** (CEGUI::EventSet *pEventSet, const std::string &sEventName, bool(T::*pObjectMember)(const CEGUI::EventArgs &), T *pObject)
disconnects object-member from an event

Protected Member Functions

- **CEGUIConnectionManager** ()
constructs the a connection-manager
- virtual **~CEGUIConnectionManager** ()
destructs/clean up the connection-manager

5.2.1 Detailed Description

this class is used to keep track of connections (event-callbacks) for any widget/EventSet created for/by a gui-object.

5.2.2 Constructor & Destructor Documentation

5.2.2.1 CEGUIConnectionManager () [inline, protected]

constructs the a connection-manager

5.2.2.2 ~CEGUIConnectionManager () [protected, virtual]

destructs/clean up the connection-manager

5.2.3 Member Function Documentation

5.2.3.1 void Connect (CEGUI::EventSet * *pEventSet*, const std::string & *sEventName*, bool(*)(const CEGUI::EventArgs &) *pFunction*)

connects static function to an event Parameters

pEventSet CETUIEventSet which includes the event

sEventName name of the event to be connected

pFunction addr of static function

5.2.3.2 void Connect (CEGUI::EventSet * *pEventSet*, const std::string & *sEventName*, bool(T::*)(const CEGUI::EventArgs &) *pObjectMember*, T * *pObject*) [inline]

connects object-member from an event Parameters

pEventSet CEGUIEventSet which includes the event

sEventName name of the event to be connected

pObjectMember (relative)addr of object member

pObject pointer to the instantiated object which owns the callback

5.2.3.3 void Disconnect (CEGUI::EventSet * *pEventSet*, const std::string & *sEventName*, bool(*)(const CEGUI::EventArgs &) *pFunction*)

disconnects static functions from an event Parameters

pEventSet CEGUIEventSet which includes the event

sEventName name of the CEGUIEvent

pFunction addr of static function

5.2.3.4 void Disconnect (CEGUI::EventSet * *pEventSet*, const std::string & *sEventName*, bool(T::*)(const CEGUI::EventArgs &) *pObjectMember*, T * *pObject*) [inline]

disconnects object-member from an event Parameters

pEventSet CEGUIEventSet which includes the event

sEventName name of the CEGUIEvent

pObjectMember (relative)addr of object member

pObject pointer to the instantiated object which owns the callback


The documentation for this class was generated from the following files:

- [ceguiconnectionmanager.h](#)
- [ceguiconnectionmanager.cpp](#)


5.4 CEGUIMemberSignature< T > Class Template Reference

objects instantiated from this class describes an object-member-"signature"

#include <inc/dtGUI/ceguiconnectionsignatures.h> Inheritance diagram for CEGUIMemberSignature< T >:



Collaboration diagram for CEGUIMemberSignature< T >:



Public Types

- typedef bool(T::* [CALLBACK_FPTR](#))(const CEGUI::EventArgs &)

Public Member Functions

- [CEGUIMemberSignature](#) (CEGUI::EventSet *pEventSet, const std::string &sEventName, const [CALLBACK_FPTR](#) pMemberFunction, const void *pObject)
construcs a connection-signature-object
- const [CALLBACK_FPTR](#) [GetFunctionPtr](#) () const
returns the pointer to the object-member
- const void * [GetObjectPtr](#) () const
returns the pointer to the object

- `bool match` (CEGUI::EventSet *pEventSet, const std::string &sEventName, const [CALLBACK_FPTR](#) pMemberFunction, const void *pObject) const
check if one signature "matches" another (empty strings and NULL-Pointer's are Wildcards, means: "match any value")
- `virtual bool operator==` (const [CEGUIMemberSignatureBase](#) &x) const
compares member-signatures

5.4.1 Detailed Description

`template<class T> class dtGUI::CEGUIMemberSignature< T >`

objects instantiated from this class describes an object-member-"signature"

5.4.2 Member Typedef Documentation

5.4.2.1 `typedef bool(T::* CALLBACK_FPTR)(const CEGUI::EventArgs &)`

5.4.3 Constructor & Destructor Documentation

5.4.3.1 `CEGUIMemberSignature (CEGUI::EventSet * pEventSet, const std::string & sEventName, const CALLBACK_FPTR pMemberFunction, const void * pObject) [inline]`

construcs a connection-signature-object

5.4.4 Member Function Documentation

5.4.4.1 `const CALLBACK_FPTR GetFunctionPtr () const [inline]`

returns the pointer to the object-member

5.4.4.2 `const void* GetObjectPtr () const [inline]`

returns the pointer to the object

5.4.4.3 `bool match (CEGUI::EventSet * pEventSet, const std::string & sEventName, const CALLBACK_FPTR pMemberFunction, const void * pObject) const [inline]`

check if one signature "matches" another (empty strings and NULL-Pointer's are Wildcards, means: "match any value")

5.4.4.4 `virtual bool operator== (const CEGUIMemberSignatureBase &) const [inline, virtual]`

compares member-signatures

Implements [CEGUIMemberSignatureBase](#).


The documentation for this class was generated from the following file:

- [ceguiconnectionsignatures.h](#)


5.5 CEGUIMemberSignatureBase Class Reference

Common interface for a member-callback-connection-signatures.

#include <inc/dtGUI/ceguiconnectionsignatures.h> Inheritance diagram for CEGUIMemberSignatureBase:



Collaboration diagram for CEGUIMemberSignatureBase:



Public Member Functions

- [CEGUIMemberSignatureBase](#) (CEGUI::EventSet *pEventSet, const std::string &sEventName)
constructs a signature for an object-member-function
- const std::string & [GetEventName](#) () const
returns the event name which is part of the signature
- const CEGUI::EventSet * [GetEventSet](#) () const
returns the event set which is part of the signature
- virtual bool [operator==](#) (const [CEGUIMemberSignatureBase](#) &) const =0
compares member-signatures

Protected Member Functions

- virtual [~CEGUIMemberSignatureBase](#) ()

Protected Attributes

- CEGUI::EventSet * [m_pEventSet](#)
- std::string [m_sEventName](#)

Friends

- class [CEGUIConnectionManager](#)

5.5.1 Detailed Description

Common interface for a member-callback-connection-signatures.

5.5.2 Constructor & Destructor Documentation

5.5.2.1 CEGUIMemberSignatureBase (CEGUI::EventSet * *pEventSet*, const std::string & *sEventName*) [inline]

constructs a signature for an object-member-function

5.5.2.2 virtual ~CEGUIMemberSignatureBase () [inline, protected, virtual]

5.5.3 Member Function Documentation

5.5.3.1 const std::string& GetEventName () const [inline]

returns the event name which is part of the signature

5.5.3.2 const CEGUI::EventSet* GetEventSet () const [inline]

returns the event set which is part of the signature

5.5.3.3 virtual bool operator==(const CEGUIMemberSignatureBase &) const [pure virtual]

compares member-signatures

Implemented in [CEGUIMemberSignature< T >](#).

5.5.4 Friends And Related Function Documentation

5.5.4.1 friend class CEGUIConnectionManager [friend]

5.5.5 Member Data Documentation

5.5.5.1 CEGUI::EventSet* m_pEventSet [protected]

5.5.5.2 std::string m_sEventName [protected]

The documentation for this class was generated from the following file:

- [ceguiconnectionsignatures.h](#)

5.6.3.4 bool HandleMouseDragged (const dtCore::Mouse * *mouse*, float *x*, float *y*)**Todo**

test System for null, throw exception if null.

5.6.3.5 bool HandleMouseMoved (const dtCore::Mouse * *mouse*, float *x*, float *y*)**Todo**

test System for null, throw exception if null.

Todo

document these magic constants from the CEUIDrawable-days.

5.6.3.6 bool HandleMouseScrolled (const dtCore::Mouse * *mouse*, int *delta*)**Todo**

test System for null, throw exception if null.


5.6.3.7 void SetWindowSize (unsigned int *width*, unsigned int *height*)

The documentation for this class was generated from the following files:

- [ceguimouselistener.h](#)
- [ceguimouselistener.cpp](#)

5.7 CEGUIRenderer Class Reference

#include <inc/dtGUI/ceguirenderer.h> Collaboration diagram for CEGUIRenderer:



Classes

- struct **MyQuad**
- struct **QuadInfo**

Public Member Functions

- [CEGUIRenderer](#) (CEGUI::uint max_quads, int width, int height, CEGUI::ImageCodec *codec=0)
- [CEGUIRenderer](#) (CEGUI::uint max_quads, CEGUI::ImageCodec *codec=0)
- virtual [~CEGUIRenderer](#) (void)
- virtual void [addQuad](#) (const CEGUI::Rect &dest_rect, float z, const CEGUI::Texture *tex, const CEGUI::Rect &texture_rect, const CEGUI::ColourRect &colours, CEGUI::QuadSplitMode quam_split_mode)
- virtual void [clearRenderList](#) (void)
- virtual CEGUI::Texture * [createTexture](#) (float size)
- virtual CEGUI::Texture * [createTexture](#) (const CEGUI::String &filename, const CEGUI::String &resource-Group)
- virtual CEGUI::Texture * [createTexture](#) (void)
- virtual void [destroyAllTextures](#) (void)
- virtual void [destroyTexture](#) (CEGUI::Texture *texture)
- virtual void [doRender](#) (void)
- virtual float [getHeight](#) (void) const
- virtual CEGUI::uint [getHorzScreenDPI](#) (void) const
- CEGUI::ImageCodec & [getImageCodec](#) (void)
- virtual CEGUI::uint [getMaxTextureSize](#) (void) const
- virtual CEGUI::Rect [getRect](#) (void) const
- virtual CEGUI::Size [getSize](#) (void) const
- virtual CEGUI::uint [getVertScreenDPI](#) (void) const
- virtual float [getWidth](#) (void) const
- virtual bool [isQueueingEnabled](#) (void) const
- void [setDisplaySize](#) (const CEGUI::Size &sz)
- void [SetGraphicsContext](#) (osg::GraphicsContext *)
- void [setImageCodec](#) (CEGUI::ImageCodec *codec)
- void [setImageCodec](#) (const CEGUI::String &codecName)
- virtual void [setQueueingEnabled](#) (bool setting)

Static Public Member Functions

- static const CEGUI::String & [getDefaultImageCodecName](#) ()
- static void [setDefaultImageCodecName](#) (const CEGUI::String &codecName)

5.7.1 Constructor & Destructor Documentation

5.7.1.1 CEGUIRenderer (CEGUI::uint *max_quads*, CEGUI::ImageCodec * *codec* = 0)

5.7.1.2 CEGUIRenderer (CEGUI::uint *max_quads*, int *width*, int *height*, CEGUI::ImageCodec * *codec* = 0)

5.7.1.3 ~CEGUIRenderer (void) [virtual]

5.7.2 Member Function Documentation

5.7.2.1 void [addQuad](#) (const CEGUI::Rect & *dest_rect*, float *z*, const CEGUI::Texture * *tex*, const CEGUI::Rect & *texture_rect*, const CEGUI::ColourRect & *colours*, CEGUI::QuadSplitMode *quam_split_mode*) [virtual]

5.7.2.2 void [clearRenderList](#) (void) [virtual]

5.7.2.3 CEGUI::Texture * [createTexture](#) (float *size*) [virtual]

5.7.2.4 CEGUI::Texture * [createTexture](#) (const CEGUI::String & *filename*, const CEGUI::String & *resourceGroup*) [virtual]

5.7.2.5 CEGUI::Texture * [createTexture](#) (void) [virtual]

5.7.2.6 void [destroyAllTextures](#) (void) [virtual]

5.7.2.7 void [destroyTexture](#) (CEGUI::Texture * *texture*) [virtual]

5.7.2.8 void [doRender](#) (void) [virtual]

5.7.2.9 const CEGUI::String & [getDefaultImageCodecName](#) () [static]

5.7.2.10 virtual float [getHeight](#) (void) const [inline, virtual]

5.7.2.11 virtual CEGUI::uint [getHorzScreenDPI](#) (void) const [inline, virtual]

5.7.2.12 CEGUI::ImageCodec & [getImageCodec](#) (void)

5.7.2.13 virtual CEGUI::uint [getMaxTextureSize](#) (void) const [inline, virtual]

5.7.2.14 virtual CEGUI::Rect [getRect](#) (void) const [inline, virtual]

5.7.2.15 virtual CEGUI::Size [getSize](#) (void) const [inline, virtual]

5.7.2.16 virtual CEGUI::uint [getVertScreenDPI](#) (void) const [inline, virtual]

5.7.2.17 virtual float [getWidth](#) (void) const [inline, virtual]

5.7.2.18 virtual bool [isQueueingEnabled](#) (void) const [inline, virtual]

5.7.2.19 void [setDefaultImageCodecName](#) (const CEGUI::String & *codecName*) [static]

5.7.2.20 void [setDisplaySize](#) (const CEGUI::Size & *sz*)

5.7.2.21 void [SetGraphicsContext](#) (osg::GraphicsContext * *gc*)

5.7.2.22 void [setImageCodec](#) (CEGUI::ImageCodec * *codec*)

5.7.2.23 void [setImageCodec](#) (const CEGUI::String & *codecName*)

5.7.2.24 virtual void [setQueueingEnabled](#) (bool *setting*) [inline, virtual]


The documentation for this class was generated from the following files:

- [ceguirenderer.h](#)
- [ceguirenderer.cpp](#)

5.8 CEGUISignatureStatic Class Reference

objects instantiated from this class describes a static-method's signature

#include <inc/dtGUI/ceguiconnectionsignatures.h> Collaboration diagram for CEGUISignatureStatic:



Public Types

- typedef bool(* [CALLBACK_FPTR](#))(const CEGUI::EventArgs &)

Public Member Functions

- [CEGUISignatureStatic](#) (CEGUI::EventSet *pEventSet, const std::string &sEventName, const [CALLBACK_FPTR](#) pFunction)
- const std::string & [GetEventName](#) () const
returns the event set which is part of the signature
- const CEGUI::EventSet * [GetEventSet](#) () const
returns the event set which is part of the signature
- const [CALLBACK_FPTR](#) [GetFunctionPtr](#) () const
- bool [match](#) (CEGUI::EventSet *pEventSet, const std::string &sEventName, const [CALLBACK_FPTR](#) pFunction) const
check if one signature "matches" another (empty strings and NULL-Pointer's are Wildcards, means: "match any value")
- virtual bool [operator==](#) (const [CEGUISignatureStatic](#) &x) const

5.8.1 Detailed Description

objects instantiated from this class describes a static-method's signature

5.8.2 Member Typedef Documentation

5.8.2.1 `typedef bool(* CALLBACK_FPTR)(const CEGUI::EventArgs &)`

5.8.3 Constructor & Destructor Documentation

5.8.3.1 `CEGUISignatureStatic (CEGUI::EventSet * pEventSet, const std::string & sEventName, const CALLBACK_FPTR pFunction) [inline]`

5.8.4 Member Function Documentation

5.8.4.1 `const std::string& GetEventName () const [inline]`

returns the event set which is part of the signature

5.8.4.2 `const CEGUI::EventSet* GetEventSet () const [inline]`

returns the event set which is part of the signature

5.8.4.3 `const CALLBACK_FPTR GetFunctionPtr () const [inline]`

5.8.4.4 `bool match (CEGUI::EventSet * pEventSet, const std::string & sEventName, const CALLBACK_FPTR pFunction) const [inline]`

check if one signature "matches" another (empty strings and NULL-Pointer's are Wildcards, means: "match any value")

5.8.4.5 `virtual bool operator==(const CEGUISignatureStatic & x) const [inline, virtual]`

The documentation for this class was generated from the following file:

- [ceguiconnectionsignatures.h](#)

5.9 CEGUITexture Class Reference

implementation of the CEGUI::Texture for OpenSceneGraph

```
#include <inc/dtGUI/ceguiTexture.h>
```

Public Member Functions

- [CEGUITexture](#) (CEGUI::Renderer *)
- [~CEGUITexture](#) ()
- virtual CEGUI::ushort [getHeight](#) () const
- virtual CEGUI::ushort [getOriginalHeight](#) (void) const
get the original height of the texture (cegui-textures are automatically resized to pot)
- virtual CEGUI::ushort [getOriginalWidth](#) (void) const
get the original with of the texture (cegui-textures are automatically resized to pot)
- const osg::Texture2D * [GetOSGTexture](#) () const
get current osg-texture
- osg::Texture2D * [GetOSGTexture](#) ()
get current osg-texture
- unsigned int [GetTextureID](#) (osg::GraphicsContext *)
get osg-texture-handle for a osg::GraphicsContext
- virtual CEGUI::ushort [getWidth](#) () const
- virtual float [getXScale](#) (void) const
- virtual float [getYScale](#) (void) const
- bool [IsFlippedHorizontal](#) () const
if true the CEGUIRenderer will flip y-coordinates
- virtual void [loadFromFile](#) (const CEGUI::String &filename, const CEGUI::String &resourceGroup)
- virtual void [loadFromMemory](#) (const void *buffPtr, CEGUI::uint buffWidth, CEGUI::uint buffHeight, CEGUI::Texture::PixelFormat pixelFormat)
- void [ResizeToMinPOT](#) (unsigned short w, unsigned short h)
- void [SetFlipHorizontal](#) (bool bX)
if set to true the CEGUIRenderer will flip y-coordinates
- void [SetOSGTexture](#) (osg::Texture2D *pTexture)
set the osg-texture that'll be used

5.9.1 Detailed Description

implementation of the CEGUI::Texture for OpenSceneGraph

5.9.2 Constructor & Destructor Documentation

5.9.2.1 CEGUITexture (CEGUI::Renderer * pRenderer)

5.9.2.2 ~CEGUITexture ()

5.9.3 Member Function Documentation

5.9.3.1 CEGUI::ushort getHeight () const [virtual]

5.9.3.2 CEGUI::ushort getOriginalHeight (void) const [virtual]

get the original height of the texture (cegui-textures are automatically resized to pot)

5.9.3.3 CEGUI::ushort getOriginalWidth (void) const [virtual]

get the original with of the texture (cegui-textures are automatically resized to pot)

5.9.3.4 const osg::Texture2D* GetOSGTexture () const [inline]

get current osg-texture

5.9.3.5 osg::Texture2D* GetOSGTexture () [inline]

get current osg-texture

5.9.3.6 unsigned int GetTextureID (osg::GraphicsContext * *pGraphicsContext*)

get osg-texture-handle for a osg::GraphicsContext

5.9.3.7 CEGUI::ushort getWidth () const [virtual]**5.9.3.8 virtual float getXScale (void) const [inline, virtual]****5.9.3.9 virtual float getYScale (void) const [inline, virtual]****5.9.3.10 bool IsFlippedHorizontal () const [inline]**

if true the CEGUIRenderer will flip y-coordinates

5.9.3.11 void loadFromFile (const CEGUI::String & *filename*, const CEGUI::String & *resourceGroup*) [virtual]**5.9.3.12 void loadFromMemory (const void * *buffPtr*, CEGUI::uint *buffWidth*, CEGUI::uint *buffHeight*, CEGUI::Texture::PixelFormat *pixelFormat*) [virtual]****5.9.3.13 void ResizeToMinPOT (unsigned short *w*, unsigned short *h*)****5.9.3.14 void SetFlipHorizontal (bool *bx*) [inline]**

if set to true the CEGUIRenderer will flip y-coordinates

5.9.3.15 void SetOSGTexture (osg::Texture2D * *pTexture*) [inline]

set the osg-texture that'll be used


The documentation for this class was generated from the following files:

- [ceguiTexture.h](#)
- [ceguiTexture.cpp](#)

5.10 CEUIDrawable Class Reference

A DeltaDrawable used to render CEGUI.

#include <inc/dtGUI/ceuidrawable.h> Collaboration diagram for CEUIDrawable:



Classes

- class **osgCEUIDrawable**

private class that ties the GUI rendering to an OSG node This is a private class that is used by the UIDrawable class.

Public Member Functions

- [CEUIDrawable](#) (dtCore::DeltaWin *win, dtCore::Keyboard *keyboard, dtCore::Mouse *mouse, dtGUI::BaseScriptModule *sm=0)
Overloaded constructor, will automatically update CEGUI when the supplied Window is resized.
- bool [AddChild](#) (dtCore::DeltaDrawable *child)
Attaches the Delta3D child's OSG graphics Node.
- bool [GetAutoResizing](#) () const
- const [CEGUIKeyboardListener](#) * [GetKeyboardListener](#) () const
- const [CEGUIMouseListener](#) * [GetMouseListener](#) () const
- const osg::Node * [GetOSGNode](#) () const
- osg::Node * [GetOSGNode](#) ()
required by DeltaDrawable
- osg::Projection * [GetProjectionNode](#) ()
Not usually needed, but this getter is provided for unusual scenarios.
- const dtGUI::CEGUIRenderer * [GetRenderer](#) () const
- dtGUI::CEGUIRenderer * [GetRenderer](#) ()
Get a pointer to the underlying [Renderer](#).

- `osg::MatrixTransform * GetTransformNode ()`
Not usually needed, but this getter is provided for unusual scenarios.
- `CEGUI::System * GetUI ()`
Get a pointer to the underlying CEGUI::System.
- `void SetAutoResizing (bool enable=true)`
Automatically notify CEGUI of DeltaWin resizes (enabled by default).
- `void SetOSGNode (osg::Node *pNode)`
- `void SetRenderBinDetails (int binNumber, const std::string &binName)`
Set the render bin details on the contained geode's state set.
- `void SetRenderingSize (int width, int height)`
Manually set the size of the rendering area (in pixels).
- `void ShutdownGUI ()`
Turns off the GUI System, no longer yielding GUI support.

Static Public Member Functions

- `static void DisplayProperties (CEGUI::Window *window, bool onlyNonDefault=true)`
Display all the properties of the supplied CEGUI::Window.

Protected Member Functions

- `virtual ~CEUIDrawable ()`
- `void OnMessage (dtCore::Base::MessageData *data)`

Protected Attributes

- `dtCore::RefPtr< osg::Geode > mGeode`
- `int mHeight`
- `dtCore::RefPtr< dtCore::Keyboard > mKeyboard`
- `dtCore::RefPtr< dtCore::Mouse > mMouse`
- `dtCore::RefPtr< osg::Node > mNode`
- `dtCore::RefPtr< osg::Projection > mProjection`
- `CEGUI::Renderer * mRenderer`
The opengl renderer we're using.
- `dtGUI::BaseScriptModule * mScriptModule`
- `dtCore::RefPtr< osg::MatrixTransform > mTransform`
- `CEGUI::System * mUI`
Pointer to the CUI_UI.
- `int mWidth`
- `dtCore::RefPtr< dtCore::DeltaWin > mWindow`
The window this UI is being rendered in.

5.10.1 Detailed Description

A DeltaDrawable used to render CEGUI. This class is a derivative of DeltaDrawable and is used to render and manage the CEGUI system. The [CEUIDrawable](#) is responsible for setting up the CEGUI system and supplying mouse and keyboard events to the UI.

To create a new GUI, instantiate a CEGUIDrawable and add it to the Scene using `Scene::AddDrawable()`. You can then use the CEGUI API to create `CEGUI::Windows` and adjust their properties.

NOTE: The CEGUIDrawable class must be instantiated *after* the application has created a valid OpenGL context (i.e., during `dtABC::Application::Config()`).

5.10.2 Constructor & Destructor Documentation

5.10.2.1 CEUIDrawable (dtCore::DeltaWin * *win*, dtCore::Keyboard * *keyboard*, dtCore::Mouse * *mouse*, dtGUI::BaseScriptModule * *sm* = 0)

Overloaded constructor, will automatically update CEGUI when the supplied Window is resized. The supplied DeltaWin will automatically be monitored for size change and pass the new size onto the CEGUI [Renderer](#).

Parameters

win : The DeltaWin to monitor for size change

sm : The [ScriptModule](#) to use for CEGUI script processing

Exceptions

dtUtil::Exception Gets thrown if CEGUI cannot be initialized

5.10.2.2 ~CEUIDrawable () [protected, virtual]

5.10.3 Member Function Documentation

5.10.3.1 bool AddChild (dtCore::DeltaDrawable * *child*)

Attaches the Delta3D child's OSG graphics Node.

5.10.3.2 void DisplayProperties (CEGUI::Window * *window*, bool *onlyNonDefault* = true) [static]

Display all the properties of the supplied CEGUI::Window. Display the properties associated with the supplied CEGUI::Window to the console.

Useful to find all the text names of the properties and see what the current values of the properties are.

Parameters

window : The window to query the properties of

onlyNonDefault : Display only properties that are not default values (default=true)

5.10.3.3 bool GetAutoResizing () const [inline]

5.10.3.4 const CEGUIKeyboardListener* GetKeyboardListener () const [inline]

5.10.3.5 const CEGUIMouseListener* GetMouseListener () const [inline]

5.10.3.6 const osg::Node* GetOSGNode () const [inline]

5.10.3.7 osg::Node* GetOSGNode () [inline]

required by DeltaDrawable

5.10.3.8 osg::Projection* GetProjectionNode () [inline]

Not usually needed, but this getter is provided for unusual scenarios.

5.10.3.9 `const dtGUI::CEGUIRenderer* GetRenderer () const [inline]`

5.10.3.10 `dtGUI::CEGUIRenderer* GetRenderer () [inline]`

Get a pointer to the underlying [Renderer](#).

5.10.3.11 `osg::MatrixTransform* GetTransformNode () [inline]`

Not usually needed, but this getter is provided for unusual scenarios.

5.10.3.12 `CEGUI::System* GetUI () [inline]`

Get a pointer to the underlying CEGUI::System.

5.10.3.13 `void OnMessage (dtCore::Base::MessageData * data) [protected]`

Todo

must we really cast here?

5.10.3.14 `void SetAutoResizing (bool enable = true) [inline]`

Automatically notify CEGUI of DeltaWin resizes (enabled by default).

5.10.3.15 `void SetOSGNode (osg::Node * pNode) [inline]`

5.10.3.16 `void SetRenderBinDetails (int binNumber, const std::string & binName)`

Set the render bin details on the contained geode's state set. Parameters

binNumber Order of the bin in relation to other bins.

binName Name of the bin.

5.10.3.17 `void SetRenderingSize (int width, int height)`

Manually set the size of the rendering area (in pixels). Set the width and height of the rendering area. Typically this is just the size of the DeltaWin the GUI is being rendered in. If AutoResizing is enabled, these values will be overwritten. Disable AutoResizing to manually control the rendered area. See also [SetAutoResizing\(\)](#)

Parameters

width : the width of the rendered area (pixels)

height : the height of the rendered area (pixels)

5.10.3.18 `void ShutdownGUI ()`

Turns off the GUI System, no longer yielding GUI support. The System will do its clean up at this time.

5.10.4 Member Data Documentation

5.10.4.1 `dtCore::RefPtr<osg::Geode> mGeode [protected]`

5.10.4.2 `int mHeight [protected]`

5.10.4.3 `dtCore::RefPtr<dtCore::Keyboard> mKeyboard [protected]`

5.10.4.4 `dtCore::RefPtr<dtCore::Mouse> mMouse [protected]`

5.10.4.5 `dtCore::RefPtr<osg::Node> mNode [protected]`

5.10.4.6 `dtCore::RefPtr<osg::Projection> mProjection [protected]`

5.10.4.7 `CEGUIRenderer* mRenderer [protected]`

The opengl renderer we're using.

5.10.4.8 dtGUI::BaseScriptModule* mScriptModule [protected]

5.10.4.9 dtCore::RefPtr<osg::MatrixTransform> mTransform [protected]

5.10.4.10 CEGUI::System* mUI [protected]

Pointer to the CUI_UI.

5.10.4.11 int mWidth [protected]

5.10.4.12 dtCore::RefPtr<dtCore::DeltaWin> mWindow [protected]

The window this UI is being rendered in.

The documentation for this class was generated from the following files:

- [ceuidrawable.h](#)
- [ceuidrawable.cpp](#)

5.11 ExceptionEnum Class Reference

#include <inc/dtGUI/guiexceptionenum.h> Collaboration diagram for ExceptionEnum:



Static Public Attributes

- static [ExceptionEnum GenericCEGUIException](#)

Protected Member Functions

- [ExceptionEnum](#) (const std::string &name)

5.11.1 Constructor & Destructor Documentation

5.11.1.1 [ExceptionEnum](#) (const std::string & *name*) [`inline`, `protected`]

5.11.2 Member Data Documentation

5.11.2.1 [ExceptionEnum GenericCEGUIException](#) [`static`]

The documentation for this class was generated from the following files:

- [guiexceptionenum.h](#)
- [guiexceptionenum.cpp](#)

- void [Disconnect](#) (const std::string &sWidgetName, const std::string &sEventName, bool(*pFunction)(const CEGUI::EventArgs &))
- void [Disconnect](#) (const std::string &sWidgetName, const std::string &sEventName, int, int)
wraps this->Disconnect(this->GetWidget(widgetName), eventName, 'wildcard', 'wildcard')
- template<class T >
void [Disconnect](#) (const std::string &sWidgetName, const std::string &sEventName, bool(T::*pObjectMember)(const CEGUI::EventArgs &), int)
wraps this->Disconnect(this->GetWidget(widgetName), eventName, pObjectMember, 'wildcard')
- template<class T >
void [Disconnect](#) (const std::string &sWidgetName, const std::string &sEventName, int, T *pObject)
wraps this->Disconnect(this->GetWidget(widgetName), eventName, 'wildcard', pObject)
- template<class T >
void [Disconnect](#) (const std::string &sWidgetName, const std::string &sEventName, bool(T::*pObjectMember)(const CEGUI::EventArgs &), T *pObject)
wraps this->Disconnect(this->GetWidget(widgetName), eventName, pObjectMember, pObject)
- osg::Geode * [GetInternalGraph](#) () const
- bool [GetIsMouseCursorVisible](#) () const
returns whether the CEGUI mouse cursor should be visible or not
- const dtCore::Keyboard * [GetKeyboard](#) () const
returns keyboard-object used by the gui for input
- dtCore::Keyboard * [GetKeyboard](#) ()
returns keyboard-object used by the gui for input
- const dtCore::Mouse * [GetMouse](#) () const
returns mouse-object from which the gui receives events
- dtCore::Mouse * [GetMouse](#) ()
returns mouse-object from which the gui receives events
- osg::Texture2D * [GetOrCreateOSGTexture](#) (const std::string &sWidgetName)
returns associated osg-texture for any widget which has the "Image" property
- const std::string [GetPrefix](#) () const
returns auto-generated prefix for the gui
- const [Widget](#) * [GetRootsheet](#) () const
returns default sheet (autogenerated root-window)
- [Widget](#) * [GetRootSheet](#) ()
returns default sheet (autogenerated root-window)
- [Widget](#) * [GetWidget](#) (const std::string &sWidgetName, const std::string &sPrefix="")
searches widget by it's name
- [Widget](#) * [LoadLayout](#) ([Widget](#) *pWidgetParent, const std::string &sFileName, const std::string &sPrefix="")
loads a layout-file and add it to the given Widget(which should a child of the gui)
- [Widget](#) * [LoadLayout](#) (const std::string &sFileName, const std::string &sPrefix="")
loads a layout-file

- void [MakeCurrent](#) () const
- void [SetCamera](#) (osg::Camera *pTargetCamera)
sets the rendertarget (camera) for the gui-object
- void [SetIsMouseCursorVisible](#) (bool val)
sets whether the CEGUI mouse cursor should be visible or not
- void [SetKeyboard](#) (dtCore::Keyboard *pObservedKeyboard)
sets keyboard-object which is used for input
- void [SetMouse](#) (dtCore::Mouse *pObservedMouse)
sets the mouse-object from which the gui receives events

Static Public Member Functions

- static void [CreateFont](#) (const std::string &)
shortcut/wrapper to CEGUI::FontManager::createFont
- static void [DestroyAllFonts](#) ()
shortcut/wrapper to CEGUI::FontManager::destroyAllFonts
- static void [DestroyFont](#) (const std::string &)
shortcut/wrapper to CEGUI::FontManager::destroyFont
- static const std::string & [GetFilePath](#) ()
returns the file path for gui-xml-data/images
- static void [LoadScheme](#) (const std::string &)
shortcut/wrapper to CEGUI::SchemeManager::loadScheme
- static void [SetFilePath](#) (const std::string &sPath)
sets the file path for all gui-objects
- static void [SetMouseCursor](#) (const std::string &setImageSetName, const std::string &setImageName)
shortcut/wrapper to CEGUI::System::getSingleton().setMouseCursor
- static void [UnloadAllSchemes](#) ()
shortcut/wrapper to CEGUI::SchemeManager::unloadAllSchemes
- static void [UnloadScheme](#) (const std::string &)
shortcut/wrapper to CEGUI::SchemeManager::unloadScheme

Protected Member Functions

- virtual [~HUD](#) ()
destructs an existing gui object

5.12.1 Detailed Description

gui-class for rendering and managing widgets any [HUD](#) can use any camera as render-target each [HUD](#) owns it's own root-sheet (See also [GetRootSheet\(\)](#)) which always fits the the whole viewport of the targeted-camera internally each [HUD](#) will use an own name-prefix for widgets(if they were created via LoadLayout/CreateWidget). so if one intend to use cegui-standard-api (example: CEGUI::WindowManager::getWindow()) window names must be prefixed by the HUD's prefix See also [GetPrefix\(\)](#) if creating new connections via Connect/Disconnect one keep in mind that these connections are handled by the gui-object and thus they will be lost on gui-object-destruction the Connect/Disconnect are inteded to handle the connection creation/destruction more easily for widgets. because of this fact it's wise to use them only for this

5.12.2 Constructor & Destructor Documentation

5.12.2.1 HUD (osg::Camera * *pTargetCamera*, dtCore::Keyboard * *pObservedKeyboard* = 0, dtCore::Mouse * *pObservedMouse* = 0, const std::string & *sName* = "HUD")

constructs a new gui object Parameters

pTargetCamera camera where the gui is drawn as hud

pObservedKeyboard observed keyboard-object for input

pObservedMouse observed mouse-object for input

sName delta3D-name of the gui-object

5.12.2.2 HUD (dtCore::Camera * *pTargetCamera*, dtCore::Keyboard * *pObservedKeyboard* = 0, dtCore::Mouse * *pObservedMouse* = 0, const std::string & *sName* = "HUD")

constructs a new gui object Parameters

pTargetCamera camera where the gui will show up (as hud)

pObservedKeyboard observed keyboard-object for input

pObservedMouse observed mouse-object for input

sName delta3D-name of the gui-object

5.12.2.3 ~HUD () [protected, virtual]

destructs an existing gui object

5.12.3 Member Function Documentation

5.12.3.1 void Connect (const std::string & *sWidgetName*, const std::string & *sEventName*, bool(*)(const CEGUI::EventArgs &) *pFunction*) [inline]

5.12.3.2 void Connect (const std::string & *sWidgetName*, const std::string & *sEventName*, bool(T::*)(const CEGUI::EventArgs &) *pObjectMember*, T * *pObject*) [inline]

wraps [CEGUIConnectionManager::Connect](#)(this->GetWidget(widgetName), eventName, pObjectMember, pObject)

5.12.3.3 void CreateFont (const std::string & *sFileName*) [static]

shortcut/wrapper to CEGUI::FontManager::createFont

5.12.3.4 Widget * CreateWidget (const std::string & *sWidgetTypeName*, const std::string & *sWidgetName* = "", const std::string & *sPrefix* = "")

creates/adds a widget to root-sheet

5.12.3.5 Widget * CreateWidget (Widget * *pParentWidget*, const std::string & *sWidgetTypeName*, const std::string & *sWidgetName* = "", const std::string & *sPrefix* = "")

creates/adds a widget to a given parent

5.12.3.6 void DestroyAllFonts () [static]

shortcut/wrapper to CEGUI::FontManager::destroyAllFonts

5.12.3.7 void DestroyFont (const std::string & *sFileName*) [static]

shortcut/wrapper to CEGUI::FontManager::destroyFont

5.12.3.8 void Disconnect (const std::string & *sWidgetName*, const std::string & *sEventName*, bool (*)(const CEGUI::EventArgs &) *pFunction*) [inline]

5.12.3.9 void Disconnect (const std::string & *sWidgetName*, const std::string & *sEventName*, int, int) [inline]

wraps this->Disconnect(this->GetWidget(widgetName), eventName, 'wildcard', 'wildcard')

5.12.3.10 void Disconnect (const std::string & *sWidgetName*, const std::string & *sEventName*, bool(T::*)(const CEGUI::EventArgs &) *pObjectMember*, int) [inline]

wraps this->Disconnect(this->GetWidget(widgetName), eventName, pObjectMember, 'wildcard')

5.12.3.11 void Disconnect (const std::string & *sWidgetName*, const std::string & *sEventName*, int, T * *pObject*) [inline]

wraps this->Disconnect(this->GetWidget(widgetName), eventName, 'wildcard', pObject)

5.12.3.12 void Disconnect (const std::string & *sWidgetName*, const std::string & *sEventName*, bool(T::*)(const CEGUI::EventArgs &) *pObjectMember*, T * *pObject*) [inline]

wraps this->Disconnect(this->GetWidget(widgetName), eventName, pObjectMember, pObject)

5.12.3.13 const std::string & GetFilePath () [static]

returns the file path for gui-xml-data/images See also [SetFilePath](#)

5.12.3.14 osg::Geode* GetInternalGraph () const [inline]

5.12.3.15 bool GetIsMouseCursorVisible () const [inline]

returns whether the CEGUI mouse cursor should be visible or not

5.12.3.16 const dtCore::Keyboard* GetKeyboard () const [inline]

returns keyboard-object used by the gui for input

5.12.3.17 dtCore::Keyboard* GetKeyboard () [inline]

returns keyboard-object used by the gui for input

5.12.3.18 const dtCore::Mouse* GetMouse () const [inline]

returns mouse-object from which the gui receives events

5.12.3.19 dtCore::Mouse* GetMouse () [inline]

returns mouse-object from which the gui receives events

5.12.3.20 osg::Texture2D * GetOrCreateOSGTexture (const std::string & *sWidgetName*)

returns associated osg-texture for any widget which has the "Image" property

5.12.3.21 const std::string GetPrefix () const

returns auto-generated prefix for the gui

5.12.3.22 const Widget* GetRootsheet () const [inline]

returns default sheet (autogenerated root-window)

5.12.3.23 Widget* GetRootSheet () [inline]

returns default sheet (autogenerated root-window)

5.12.3.24 Widget * GetWidget (const std::string & *sWidgetName*, const std::string & *sPrefix* = "")

searches widget by it's name

5.12.3.25 Widget * LoadLayout (Widget * *pWidgetParent*, const std::string & *sFileName*, const std::string & *sPrefix* = "")

loads a layout-file and add it to the given Widget(which should a child of the gui)

5.12.3.26 Widget * LoadLayout (const std::string & *sFileName*, const std::string & *sPrefix* = "")

loads a layout-file

5.12.3.27 void LoadScheme (const std::string & *sFileName*) [static]

shortcut/wrapper to CEGUI::SchemeManager::loadScheme

5.12.3.28 void MakeCurrent () const**5.12.3.29 void SetCamera (osg::Camera * *pTargetCamera*)**

sets the rendertarget (camera) for the gui-object

5.12.3.30 void SetFilePath (const std::string & *sPath*) [static]

sets the file path for all gui-objects

5.12.3.31 void SetIsMouseCursorVisible (bool *val*) [inline]

sets whether the CEGUI mouse cursor should be visible or not

5.12.3.32 void SetKeyboard (dtCore::Keyboard * *pObservedKeyboard*)

sets keyboard-object which is used for input

5.12.3.33 void SetMouse (dtCore::Mouse * *pObservedMouse*)

sets the mouse-object from which the gui receives events

5.12.3.34 void SetMouseCursor (const std::string & *smagesetName*, const std::string & *smageName*) [static]

shortcut/wrapper to CEGUI::System::getSingleton().setMouseCursor

5.12.3.35 void UnloadAllSchemes () [static]

shortcut/wrapper to CEGUI::SchemeManager::unloadAllSchemes

5.12.3.36 void UnloadScheme (const std::string & *sFileName*) [static]

shortcut/wrapper to CEGUI::SchemeManager::unloadScheme

The documentation for this class was generated from the following files:

- [hud.h](#)
- [hud.cpp](#)

5.13 Renderer Class Reference

Simple CEGui rendering class based on the CEGUI::OpenGLRender class.

```
#include <inc/dtGUI/renderer.h>
```

Public Member Functions

- [Renderer](#) (unsigned int max_quads=0, int width=0, int height=0)
- [~Renderer](#) ()
- virtual CEGUI::ResourceProvider * [createResourceProvider](#) ()
Create the [ResourceProvider](#) (a [dtGUI::ResourceProvider](#)).

5.13.1 Detailed Description

Simple CEGui rendering class based on the CEGUI::OpenGLRender class.

5.13.2 Constructor & Destructor Documentation

5.13.2.1 [Renderer](#) (unsigned int *max_quads* = 0, int *width* = 0, int *height* = 0)

Todo

deprecate this unnecessary ctor

5.13.2.2 [~Renderer](#) () [inline]

5.13.3 Member Function Documentation

5.13.3.1 CEGUI::ResourceProvider * [createResourceProvider](#) (void) [virtual]

Create the [ResourceProvider](#) (a [dtGUI::ResourceProvider](#)).

The documentation for this class was generated from the following files:

- [renderer.h](#)
- [renderer.cpp](#)

5.14 ResourceProvider Class Reference

A simple CEGUI [ResourceProvider](#) based on the CEGUI::DefaultResourceProvider.

```
#include <inc/dtGUI/resourceprovider.h>
```

Public Member Functions

- [ResourceProvider](#) ()
- [~ResourceProvider](#) ()
- void [loadRawDataContainer](#) (const CEGUI::String &filename, CEGUI::RawDataContainer &output, const CEGUI::String &resourceGroup)
Load the data of the supplied filename.

5.14.1 Detailed Description

A simple CEGUI [ResourceProvider](#) based on the CEGUI::DefaultResourceProvider. Add the functionality of using search paths to find the data files used by CEGUI.

See also [SetDataFilePathList\(\)](#)

5.14.2 Constructor & Destructor Documentation

5.14.2.1 [ResourceProvider](#) ()

5.14.2.2 [~ResourceProvider](#) () [inline]

5.14.3 Member Function Documentation

5.14.3.1 void [loadRawDataContainer](#) (const CEGUI::String & *filename*, CEGUI::RawDataContainer & *output*, const CEGUI::String & *resourceGroup*)

Load the data of the supplied filename. This will load the file with the supplied filename using the search paths find the files.

See also [SetDataFilePathList\(\)](#)


The documentation for this class was generated from the following files:

- [resourceprovider.h](#)
- [resourceprovider.cpp](#)


5.15 ScriptModule Class Reference

[ScriptModule](#) is the binding from CEGUI::Events to specific application callbacks.

#include <inc/dtGUI/scriptmodule.h> Inheritance diagram for ScriptModule:



Collaboration diagram for ScriptModule:



Public Types

- typedef `std::map< std::string, HandlerFunctor >` [CallbackRegistry](#)
- typedef `dtUtil::Functor< bool, TYPELIST_1(const CEGUI::EventArgs &)>` [HandlerFunctor](#)
- typedef `bool(* STATIC_FUNCTION)(const CEGUI::EventArgs &e)`

Public Member Functions

- [ScriptModule](#) ()
- virtual `~ScriptModule ()`
- bool [AddCallback](#) (const `std::string` &name, const [HandlerFunctor](#) &callback)
Add a non-static callback handler.
- bool [AddCallback](#) (const `std::string` &name, [STATIC_FUNCTION](#) func)
Add a static callback handler.

- virtual bool [executeScriptedEventHandler](#) (const CEGUI::String &handler_name, const CEGUI::EventArgs &ea)

Uses the map of strings to functions to execute a function to handle the EventArgs.

- virtual void [executeScriptFile](#) (const CEGUI::String &filename, const CEGUI::String &resourceGroup="")
- virtual int [executeScriptGlobal](#) (const CEGUI::String &function_name)
- virtual void [executeString](#) (const CEGUI::String &str)
- const [CallbackRegistry](#) & [GetRegistry](#) () const

Returns the StaticRegistry.

5.15.1 Detailed Description

[ScriptModule](#) is the binding from CEGUI::Events to specific application callbacks. Create an instance of this class, and provide it as a parameter during construction of a [CEUIDrawable](#) instance. Add new handlers with the [AddCallback](#) function.

5.15.2 Member Typedef Documentation

5.15.2.1 typedef std::map<std::string,HandlerFunctor> [CallbackRegistry](#)

5.15.2.2 typedef dtUtil::Functor<bool,TYPELIST_1(const CEGUI::EventArgs&)> [HandlerFunctor](#)

5.15.2.3 typedef bool(* [STATIC_FUNCTION](#))(const CEGUI::EventArgs &e)

Todo

test to know if this typedef can support just NonMemberFunction, not requiring them to be static.

5.15.3 Constructor & Destructor Documentation

5.15.3.1 [ScriptModule](#) ()

5.15.3.2 [~ScriptModule](#) () [virtual]

5.15.4 Member Function Documentation

5.15.4.1 bool [AddCallback](#) (const std::string & *name*, const [HandlerFunctor](#) & *callback*)

Add a non-static callback handler. Example:

```
class App
{
    ...
public:
    bool OnClick( const CEGUI::EventArgs &e );
    ...
}

...
App *mApp = new App();

dtGUI::ScriptModule::HandlerFunctor handler( dtUtil::MakeFunctor( &App::OnClick
    , mApp ) );
mScriptModule->AddCallback("OnDoSomething", handler );
...
```

Parameters

name is the string representation of the handler function to be executed for the CEGUI::Event.

func is an instance of a function object to be called when the CEGUI::Event is activated.

Attention An attempt was made to make an implementation with the signature `template<typename InstT> bool AddCallback(const std::string& name, bool (InstT::*MemFun)(const CEGUI::EventArgs&), InstT* instance)` but somehow creating the [HandlerFunctor](#) internal to the function caused some problems.

5.15.4.2 **bool AddCallback (const std::string & name, STATIC_FUNCTION func)**

Add a static callback handler. Example:

```
class MyClass
{
    ...
    static bool OnClick( const CEGUI::EventArgs &e );
    ...
}

...
mScriptModule->AddCallback("OnDoSomething", &OnClick);
...
```

Parameters

name is the string representation of the handler function to be executed for the CEGUI::Event.

func is the pointer to the function to be called when the CEGUI::Event is activated.

5.15.4.3 **bool executeScriptedEventHandler (const CEGUI::String & handler_name, const CEGUI::EventArgs & ea) [virtual]**

Uses the map of strings to functions to execute a function to handle the EventArgs. This function is called by CEGUI::System when a CEGUI::Window throws an CEGUI::Event

Implements [BaseScriptModule](#).

5.15.4.4 **void executeScriptFile (const CEGUI::String & filename, const CEGUI::String & resourceGroup = "") [virtual]**

Implements [BaseScriptModule](#).

5.15.4.5 **int executeScriptGlobal (const CEGUI::String & function_name) [virtual]**

Implements [BaseScriptModule](#).

5.15.4.6 **void executeString (const CEGUI::String & str) [virtual]**

Implements [BaseScriptModule](#).

5.15.4.7 **const CallbackRegistry& GetRegistry () const [inline]**

Returns the StaticRegistry.

The documentation for this class was generated from the following files:

- [scriptmodule.h](#)
- [scriptmodule.cpp](#)


File Documentation

6.1 bascriptmodule.h File Reference


```
#include <CEGUI/CEGUIScriptModule.h>
```

```
#include <dtGUI/export.h>
```

Include dependency graph for bascriptmodule.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [BaseScriptModule](#)
An abstract interface for classes used by [CEUIDrawable](#).


Namespaces

- namespace [dtGUI](#)
The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.2 ceguiconnectionmanager.cpp File Reference

```
#include <dtGUI/ceguiconnectionmanager.h>
```


Include dependency graph for ceguiconnectionmanager.cpp:



6.3 ceguiconnectionmanager.h File Reference

```
#include <string>
#include <map>
#include <dtGUI/ceguintegrationmanager.h>
#include <CEGUI/CEGUIWindow.h>
#include <CEGUI/CEGUIEvent.h>
#include <CEGUI/CEGUIInputEvent.h>
#include <CEGUI/CEGUIEventSet.h>
#include <CEGUI/CEGUIEventArgs.h>
#include <CEGUI/CEGUISubscriberSlot.h>
#include <dtUtil/log.h>
```

This graph shows which files directly or indirectly include this file:



Classes

- class [CEGUIConnectionManager](#)
this class is used to keep track of connections (event-callbacks) for any widget/EventSet created for/by a gui-object.


Namespaces

- namespace [dtGUI](#)
The dtGUI namespace contains the functionality to render and control OpenGL graphical user interfaces.


6.4 ceguiconnectionsignatures.h File Reference

```
#include <string>
```

Include dependency graph for ceguiconnectionsignatures.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CEGUIMemberSignature< T >](#)
objects instantiated from this class describes an object-member-"signature"
- class [CEGUIMemberSignatureBase](#)
Common interface for a member-callback-connection-signatures.
- class [CEGUISignatureStatic](#)
objects instantiated from this class describes a static-method's signature

Namespaces

- namespace [dtGUI](#)
The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.5 ceguikeyboardlistener.cpp File Reference


```
#include <dtGUI/ceguikeyboardlistener.h>
```

```
#include <dtGUI/hud.h>
```

```
#include <CEGUI/CEGUISystem.h>
```

```
#include <osgGA/GUIEventAdapter>
```

Include dependency graph for ceguikeyboardlistener.cpp:




6.6 ceguikeyboardlistener.h File Reference

```
#include <dtCore/keyboard.h>
```


```
#include <CEGUI/CEGUIInputEvent.h>
```

```
#include <dtGUI/export.h>
```

Include dependency graph for ceguikeyboardlistener.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CEGUIKeyboardListener](#)

Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.7 ceguimouselistener.cpp File Reference

```
#include <dtGUI/ceguimouselistener.h>
```


```
#include <dtGUI/hud.h>
```

```
#include <CEGUI/CEGUIInputEvent.h>
```

```
#include <CEGUI/CEGUISystem.h>
```

```
#include <dtUtil/mathdefines.h>
```

Include dependency graph for ceguimouselistener.cpp:




6.8 ceguiMouseListener.h File Reference


```
#include <dtCore/mouse.h>
```

```
#include <dtGUI/export.h>
```

Include dependency graph for ceguiMouseListener.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CEGUIMouseListener](#)
A mouse device listener to inject input to CEGUI.

Namespaces

- namespace [dtGUI](#)
The *dtGUI* namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.9 ceguirenderer.cpp File Reference

```
#include <dtGUI/ceguirenderer.h>
#include <dtGUI/ceguitexture.h>
#include <dtUtil/macros.h>
#include <osg/GL>
#include <osg/GLU>
#include <iostream>
#include <CEGUI/CEGUIExceptions.h>
#include <CEGUI/CEGUIEventArgs.h>
#include <CEGUI/CEGUIImageCodec.h>
#include <CEGUI/CEGUIDynamicModule.h>
#include <CEGUI/CEGUIBase.h>
#include <CEGUI/CEGUITexture.h>
#include <CEGUI/CEGUILogger.h>
```

Defines

- #define [S_\(X\) #X](#)
- #define [STRINGIZE\(X\) S_\(X\)](#)

6.9.1 Define Documentation

6.9.1.1 #define [S_\(X\) #X](#)

6.9.1.2 #define [STRINGIZE\(X\) S_\(X\)](#)

6.10 ceguirenderer.h File Reference

```
#include <list>
```


```
#include <set>
```

```
#include <dtGUI/export.h>
```


```
#include <osg/GraphicsContext>
```

```
#include <CEGUI/CEGUIRenderer.h>
```

Include dependency graph for ceguirenderer.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CEGUIRenderer](#)
- struct **MyQuad**
- struct **QuadInfo**

Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

Defines

- #define [OGLRENDERER_VBUFF_CAPACITY](#) 4096


6.10.1 Define Documentation

6.10.1.1 #define OGLRENDERER_VBUFF_CAPACITY 4096

6.11 ceguitexture.cpp File Reference

```
#include <dtGUI/ceguitexture.h>
#include <dtGUI/ceguirenderer.h>
#include <osg/GraphicsContext>
#include <osg/Image>
#include <osg/Texture2D>
#include <CEGUI/CEGUIExceptions.h>
#include <CEGUI/CEGUISystem.h>
#include <CEGUI/CEGUIImageCodec.h>
#include <iostream>
```

Include dependency graph for ceguitexture.cpp:




6.12 ceguitexture.h File Reference

```
#include <dtGUI/export.h>
```


```
#include <osg/Texture2D>
```

```
#include <CEGUI/CEGUITexture.h>
```

Include dependency graph for ceguitexture.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CEGUITexture](#)
implementation of the CEGUI::Texture for OpenSceneGraph

Namespaces

- namespace [dtGUI](#)
The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.


6.13 ceuidrawable.cpp File Reference

```
#include <CEGUI/CEGUIPropertySet.h>
#include <CEGUI/CEGUISystem.h>
#include <CEGUI/CEGUIWindow.h>
#include <CEGUI/CEGUIExceptions.h>
#include <CEGUI/CEGUIVersion.h>
#include <dtGUI/ceuidrawable.h>
#include <dtGUI/ceguimouselistener.h>
#include <dtGUI/ceguikeyboardlistener.h>
#include <dtGUI/basescriptmodule.h>
#include <dtGUI/guiexceptionenum.h>
#include <dtGUI/resourceprovider.h>
#include <dtGUI/ceguirenderer.h>
#include <dtCore/exceptionenum.h>
#include <dtUtil/exception.h>
#include <dtCore/deltawin.h>
#include <dtCore/system.h>
#include <dtUtil/log.h>
#include <dtGUI/renderer.h>
#include <osg/Geode>
#include <osg/Projection>
#include <osg/MatrixTransform>
#include <osg/State>
```


6.14 ceuidrawable.h File Reference

```
#include <dtCore/deltadrawable.h>
#include <dtCore/refptr.h>
#include <dtGUI/export.h>
#include <osg/Drawable>
#include <osg/CopyOp>
#include <osg/Node>
```

Include dependency graph for ceuidrawable.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [CEUIDrawable](#)
A *DeltaDrawable* used to render CEGUI.
- class **osgCEUIDrawable**
private class that ties the GUI rendering to an OSG node This is a private class that is used by the *UIDrawable* class.

Namespaces


- namespace [dtCore](#)
- namespace [dtGUI](#)
The *dtGUI* namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.15 dtgui.h File Reference

```
#include <dtGUI/ceuidrawable.h>
```

```
#include <dtGUI/scriptmodule.h>
```

Include dependency graph for dtgui.h:



Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.16 export.h File Reference

Defines

- #define [DT_GUI_EXPORT](#)


6.16.1 Define Documentation

6.16.1.1 #define DT_GUI_EXPORT

6.17 guiexceptionenum.cpp File Reference

```
#include <dtGUI/guiexceptionenum.h>
```

Include dependency graph for guiexceptionenum.cpp:



Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

Functions

- [IMPLEMENT_ENUM](#) (ExceptionEnum)


6.18 guiexceptionenum.h File Reference

```
#include <dtUtil/enumeration.h>
```


```
#include <dtUtil/exception.h>
```

```
#include <dtGUI/export.h>
```

Include dependency graph for guiexceptionenum.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [ExceptionEnum](#)

Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.19 hud.cpp File Reference

```
#include <dtGUI/hud.h>
#include <dtGUI/ceguirenderer.h>
#include <dtGUI/ceguiimage.h>
#include <CEGUI/CEGUI.h>
#include <CEGUI/CEGUIDefaultResourceProvider.h>
#include <CEGUI/CEGUIPropertySet.h>
#include <CEGUI/CEGUISystem.h>
#include <CEGUI/CEGUIWindow.h>
#include <CEGUI/CEGUIWindowManager.h>
#include <CEGUI/CEGUIImageset.h>
#include <CEGUI/CEGUIImagesetManager.h>
#include <CEGUI/CEGUIExceptions.h>
#include <CEGUI/CEGUIVersion.h>
#include <CEGUI/CEGUIXMLParser.h>
#include <CEGUI/CEGUITexture.h>
#include <CEGUI/CEGUIPropertyHelper.h>
#include <CEGUI/CEGUISchemeManager.h>
#include <dtCore/system.h>
#include <dtCore/globals.h>
#include <dtCore/mouse.h>
#include <dtCore/camera.h>
#include <dtCore/keyboard.h>
#include <dtCore/deltadrawable.h>
#include <dtUtil/log.h>
#include <dtUtil/macros.h>
#include <osg/GraphicsContext>
#include <osg/State>
#include <osg/Camera>
#include <osg/Texture2D>
#include <osg/Geode>
#include <sstream>
```

Functions

- std::string [GetCEGUIPrefix](#) (CEGUI::Window *win)


6.19.1 Function Documentation

6.19.1.1 std::string GetCEGUIPrefix (CEGUI::Window * win)

6.20 hud.h File Reference

```
#include <map>
#include <string>
#include <dtGUI/export.h>
#include <dtGUI/ceguiconnectionmanager.h>
#include <dtGUI/ceguimouselistener.h>
#include <dtGUI/ceguikeyboardlistener.h>
#include <dtGUI/widget.h>
#include <dtCore/refptr.h>
#include <dtCore/base.h>
#include <osg/Drawable>
```

This graph shows which files directly or indirectly include this file:



Classes

- struct **GUIViewport**
internal viewport-representation
- class **HUD**
gui-class for rendering and managing widgets
- class **HUDDrawable**
an osg::Drawable which will render a provided(defined via the constructor) gui

Namespaces

- namespace **dtCore**
- namespace **dtGUI**
The dtGUI namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.21 mainpage.h File Reference

6.21.1 Detailed Description


This file contains Doxygen special commands and text for the [Main Page](#) and some other minor aspects of this documentation. It is not part of Delta3D.

6.22 renderer.cpp File Reference

```
#include <dtGUI/renderer.h>
```

```
#include <dtGUI/resourceprovider.h>
```

Include dependency graph for renderer.cpp:




6.23 renderer.h File Reference

```
#include <dtGUI/export.h>
```


```
#include <CEGUI/CEGUIVersion.h>
```

```
#include <CEGUI/renderers/OpenGLGUIRenderer/openglrenderer.h>
```

Include dependency graph for renderer.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [Renderer](#)

Simple CEGui rendering class based on the CEGUI::OpenGLRender class.

Namespaces

- namespace [dtGUI](#)

The dtGUI namespace contains the functionality to render and control OpenGL graphical user interfaces.

6.24 resourceprovider.cpp File Reference


```
#include <CEGUI/CEGUIExceptions.h>
```

```
#include <dtGUI/resourceprovider.h>
```

```
#include <dtCore/globals.h>
```

```
#include <dtUtil/log.h>
```

Include dependency graph for resourceprovider.cpp:




6.25 resourceprovider.h File Reference


```
#include <dtGUI/export.h>
```

```
#include <CEGUI/CEGUIDefaultResourceProvider.h>
```

Include dependency graph for resourceprovider.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [ResourceProvider](#)

A simple CEGUI [ResourceProvider](#) based on the CEGUI::DefaultResourceProvider.

Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.


6.26 scriptmodule.cpp File Reference

```
#include <dtGUI/scriptmodule.h>
```

```
#include <dtUtil/log.h>
```

```
#include <CEGUI/CEGUIEventSet.h>
```

Include dependency graph for scriptmodule.cpp:



6.27 scriptmodule.h File Reference

```
#include <dtGUI/basescriptmodule.h>
```


```
#include <map>
```

```
#include <queue>
```


```
#include <string>
```

```
#include <dtUtil/functor.h>
```

Include dependency graph for scriptmodule.h:



This graph shows which files directly or indirectly include this file:



Classes

- class [ScriptModule](#)
ScriptModule is the binding from CEGUI::Events to specific application callbacks.


Namespaces

- namespace [dtGUI](#)
The dtGUI namespace contains the functionality to render and control OpenGL graphical user interfaces.


6.28 widget.h File Reference

```
#include <CEGUI/CEGUIWindow.h>
```

Include dependency graph for widget.h:



This graph shows which files directly or indirectly include this file:



Namespaces

- namespace [dtGUI](#)

The [dtGUI](#) namespace contains the functionality to render and control OpenGL graphical user interfaces.

Typedefs

- typedef CEGUI::Window [Widget](#)

Index

- Symbols -

- ~BaseScriptModule
 - dtGUI::BaseScriptModule, 13
- ~CEGUIConnectionManager
 - dtGUI::CEGUIConnectionManager, 16
- ~CEGUIKeyboardListener
 - dtGUI::CEGUIKeyboardListener, 17
- ~CEGIMemberSignatureBase
 - dtGUI::CEGIMemberSignatureBase, 21
- ~CEGUIMouseListener
 - dtGUI::CEGUIMouseListener, 22
- ~CEGUIRenderer
 - dtGUI::CEGUIRenderer, 25
- ~CEGUITexture
 - dtGUI::CEGUITexture, 28
- ~CEUIDrawable
 - dtGUI::CEUIDrawable, 32
- ~HUD
 - dtGUI::HUD, 39
- ~Renderer
 - dtGUI::Renderer, 42
- ~ResourceProvider
 - dtGUI::ResourceProvider, 43
- ~ScriptModule
 - dtGUI::ScriptModule, 45

- A -

- AddCallback
 - dtGUI::ScriptModule, 45
- AddChild
 - dtGUI::CEUIDrawable, 32
- addQuad
 - dtGUI::CEGUIRenderer, 25

- B -

- BaseScriptModule
 - dtGUI::BaseScriptModule, 13
- basescriptmodule.h, 47

- C -

- CALLBACK_FPTR
 - dtGUI::CEGIMemberSignature, 19
 - dtGUI::CEGUISignatureStatic, 27
- CallbackRegistry
 - dtGUI::ScriptModule, 45
- CEGUIConnectionManager
 - dtGUI::CEGUIConnectionManager, 16
 - dtGUI::CEGIMemberSignatureBase, 21
- ceguiconnectionmanager.cpp, 48
- ceguiconnectionmanager.h, 49
- ceguiconnectionsignatures.h, 50
- CEGUIKeyboardListener
 - dtGUI::CEGUIKeyboardListener, 17
- ceguikeyboardlistener.cpp, 51
- ceguikeyboardlistener.h, 52
- CEGIMemberSignature
 - dtGUI::CEGIMemberSignature, 19
- CEGIMemberSignatureBase
 - dtGUI::CEGIMemberSignatureBase, 21
- CEGUIMouseListener

- dtGUI::CEGUIMouseListener, 22
- ceguimouselistener.cpp, 53
- ceguimouselistener.h, 54
- CEGUIRenderer
 - dtGUI::CEGUIRenderer, 25
- ceguirenderer.cpp, 55
 - S_, 55
 - STRINGIZE, 55
- ceguirenderer.h, 56
 - OGLRENDERER_VBUFF_CAPACITY, 56
- CEGUISignatureStatic
 - dtGUI::CEGUISignatureStatic, 27
- CEGUITexture
 - dtGUI::CEGUITexture, 28
- ceguitexture.cpp, 57
- ceguitexture.h, 58
- CEUIDrawable
 - dtGUI::CEUIDrawable, 32
- ceuidrawable.cpp, 59
- ceuidrawable.h, 60
- clearRenderList
 - dtGUI::CEGUIRenderer, 25
- Connect
 - dtGUI::CEGUIConnectionManager, 16
 - dtGUI::HUD, 39
- CreateFont
 - dtGUI::HUD, 39
- createResourceProvider
 - dtGUI::Renderer, 42
- createTexture
 - dtGUI::CEGUIRenderer, 25
- CreateWidget
 - dtGUI::HUD, 39

- D -

- DestroyAllFonts
 - dtGUI::HUD, 39
- destroyAllTextures
 - dtGUI::CEGUIRenderer, 25
- DestroyFont
 - dtGUI::HUD, 39
- destroyTexture
 - dtGUI::CEGUIRenderer, 25
- Disconnect
 - dtGUI::CEGUIConnectionManager, 16
 - dtGUI::HUD, 39, 40
- DisplayProperties
 - dtGUI::CEUIDrawable, 32
- doRender
 - dtGUI::CEGUIRenderer, 25
- DT_GUI_EXPORT
 - export.h, 62
- dtCore, 9
- dtGUI, 10
 - IMPLEMENT_ENUM, 11
 - Widget, 11
- dtgui.h, 61
- dtGUI::BaseScriptModule, 13
 - ~BaseScriptModule, 13
 - BaseScriptModule, 13

- executeScriptedEventHandler, 13
- executeScriptFile, 14
- executeScriptGlobal, 14
- executeString, 14
- dtGUI::CEGUIConnectionManager, 15
 - ~CEGUIConnectionManager, 16
 - CEGUIConnectionManager, 16
 - Connect, 16
 - Disconnect, 16
- dtGUI::CEGUIKeyboardListener, 17
 - ~CEGUIKeyboardListener, 17
 - CEGUIKeyboardListener, 17
 - HandleKeyPressed, 17
 - HandleKeyReleased, 17
 - HandleKeyTyped, 17
 - KeyboardKeyToKeyScan, 17
- dtGUI::CEGUIMemberSignature, 18
 - CALLBACK_FPTR, 19
 - CEGUIMemberSignature, 19
 - GetFunctionPtr, 19
 - GetObjectPtr, 19
 - match, 19
 - operator==, 19
- dtGUI::CEGUIMemberSignatureBase, 20
 - ~CEGUIMemberSignatureBase, 21
 - CEGUIConnectionManager, 21
 - CEGUIMemberSignatureBase, 21
 - GetEventName, 21
 - GetEventSet, 21
 - m_pEventSet, 21
 - m_sEventName, 21
 - operator==, 21
- dtGUI::CEGUIMouseListener, 22
 - ~CEGUIMouseListener, 22
 - CEGUIMouseListener, 22
 - HandleButtonClicked, 22
 - HandleButtonPressed, 22
 - HandleButtonReleased, 22
 - HandleMouseDragged, 22
 - HandleMouseMoved, 23
 - HandleMouseScrolled, 23
 - SetWindowSize, 23
- dtGUI::CEGUIRenderer, 24
 - ~CEGUIRenderer, 25
 - addQuad, 25
 - CEGUIRenderer, 25
 - clearRenderList, 25
 - createTexture, 25
 - destroyAllTextures, 25
 - destroyTexture, 25
 - doRender, 25
 - getDefaultImageCodecName, 25
 - getHeight, 25
 - getHorzScreenDPI, 25
 - getImageCodec, 25
 - getMaxTextureSize, 25
 - getRect, 25
 - getSize, 25
 - getVertScreenDPI, 25
 - getWidth, 25
 - isQueueingEnabled, 25
 - setDefaultImageCodecName, 25
 - setDisplaySize, 25
 - SetGraphicsContext, 25
 - setImageCodec, 25
 - setQueueingEnabled, 25
- dtGUI::CEGUISignatureStatic, 26
 - CALLBACK_FPTR, 27
 - CEGUISignatureStatic, 27
 - GetEventName, 27
 - GetEventSet, 27
 - GetFunctionPtr, 27
 - match, 27
 - operator==, 27
- dtGUI::CEGUITexture, 28
 - ~CEGUITexture, 28
 - CEGUITexture, 28
 - getHeight, 28
 - getOriginalHeight, 28
 - getOriginalWidth, 28
 - GetOSGTexture, 29
 - GetTextureID, 29
 - getWidth, 29
 - getXScale, 29
 - getYScale, 29
 - IsFlippedHorizontal, 29
 - loadFromFile, 29
 - loadFromMemory, 29
 - ResizeToMinPOT, 29
 - SetFlipHorizontal, 29
 - SetOSGTexture, 29
- dtGUI::CEUIDrawable, 30
 - ~CEUIDrawable, 32
 - AddChild, 32
 - CEUIDrawable, 32
 - DisplayProperties, 32
 - GetAutoResizing, 32
 - GetKeyboardListener, 32
 - GetMouseListener, 32
 - GetOSGNode, 32
 - GetProjectionNode, 32
 - GetRenderer, 32, 33
 - GetTransformNode, 33
 - GetUI, 33
 - mGeode, 33
 - mHeight, 33
 - mKeyboard, 33
 - mMouse, 33
 - mNode, 33
 - mProjection, 33
 - mRenderer, 33
 - mScriptModule, 33
 - mTransform, 34
 - mUI, 34
 - mWidth, 34
 - mWindow, 34
 - OnMessage, 33
 - SetAutoResizing, 33
 - SetOSGNode, 33
 - SetRenderBinDetails, 33
 - SetRenderingSize, 33
 - ShutdownGUI, 33
- dtGUI::ExceptionEnum, 35
 - ExceptionEnum, 35
 - GenericCEGUIException, 35
- dtGUI::HUD, 36
 - ~HUD, 39
 - Connect, 39
 - CreateFont, 39
 - CreateWidget, 39
 - DestroyAllFonts, 39
 - DestroyFont, 39

- Disconnect, [39](#), [40](#)
 - GetFilePath, [40](#)
 - GetInternalGraph, [40](#)
 - GetIsMouseCursorVisible, [40](#)
 - GetKeyboard, [40](#)
 - GetMouse, [40](#)
 - GetOrCreateOSGTexture, [40](#)
 - GetPrefix, [40](#)
 - GetRootSheet, [40](#)
 - GetRootsheet, [40](#)
 - GetWidget, [40](#)
 - HUD, [39](#)
 - LoadLayout, [40](#)
 - LoadScheme, [41](#)
 - MakeCurrent, [41](#)
 - SetCamera, [41](#)
 - SetFilePath, [41](#)
 - SetIsMouseCursorVisible, [41](#)
 - SetKeyboard, [41](#)
 - SetMouse, [41](#)
 - SetMouseCursor, [41](#)
 - UnloadAllSchemes, [41](#)
 - UnloadScheme, [41](#)
 - dtGUI::Renderer, [42](#)
 - ~Renderer, [42](#)
 - createResourceProvider, [42](#)
 - Renderer, [42](#)
 - dtGUI::ResourceProvider, [43](#)
 - ~ResourceProvider, [43](#)
 - loadRawDataContainer, [43](#)
 - ResourceProvider, [43](#)
 - dtGUI::ScriptModule, [44](#)
 - ~ScriptModule, [45](#)
 - AddCallback, [45](#)
 - CallbackRegistry, [45](#)
 - executeScriptedEventHandler, [46](#)
 - executeScriptFile, [46](#)
 - executeScriptGlobal, [46](#)
 - executeString, [46](#)
 - GetRegistry, [46](#)
 - HandlerFunctor, [45](#)
 - ScriptModule, [45](#)
 - STATIC_FUNCTION, [45](#)
- E -**
- ExceptionEnum
 - dtGUI::ExceptionEnum, [35](#)
 - executeScriptedEventHandler
 - dtGUI::BaseScriptModule, [13](#)
 - dtGUI::ScriptModule, [46](#)
 - executeScriptFile
 - dtGUI::BaseScriptModule, [14](#)
 - dtGUI::ScriptModule, [46](#)
 - executeScriptGlobal
 - dtGUI::BaseScriptModule, [14](#)
 - dtGUI::ScriptModule, [46](#)
 - executeString
 - dtGUI::BaseScriptModule, [14](#)
 - dtGUI::ScriptModule, [46](#)
 - export.h, [62](#)
 - DT_GUI_EXPORT, [62](#)
- G -**
- GenericCEGUIException
 - dtGUI::ExceptionEnum, [35](#)
 - GetAutoResizing
 - dtGUI::CEUIDrawable, [32](#)
 - GetCEGUIPrefix
 - hud.cpp, [65](#)
 - getDefaultImageCodecName
 - dtGUI::CEGUIRenderer, [25](#)
 - GetEventName
 - dtGUI::CEGUISignatureBase, [21](#)
 - dtGUI::CEGUISignatureStatic, [27](#)
 - GetEventSet
 - dtGUI::CEGUISignatureBase, [21](#)
 - dtGUI::CEGUISignatureStatic, [27](#)
 - GetFilePath
 - dtGUI::HUD, [40](#)
 - GetFunctionPtr
 - dtGUI::CEGUISignature, [19](#)
 - dtGUI::CEGUISignatureStatic, [27](#)
 - getHeight
 - dtGUI::CEGUIRenderer, [25](#)
 - dtGUI::CEGUITexture, [28](#)
 - getHorzScreenDPI
 - dtGUI::CEGUIRenderer, [25](#)
 - getImageCodec
 - dtGUI::CEGUIRenderer, [25](#)
 - GetInternalGraph
 - dtGUI::HUD, [40](#)
 - GetIsMouseCursorVisible
 - dtGUI::HUD, [40](#)
 - GetKeyboard
 - dtGUI::HUD, [40](#)
 - GetKeyboardListener
 - dtGUI::CEUIDrawable, [32](#)
 - getMaxTextureSize
 - dtGUI::CEGUIRenderer, [25](#)
 - GetMouse
 - dtGUI::HUD, [40](#)
 - GetMouseListener
 - dtGUI::CEUIDrawable, [32](#)
 - GetObjectPtr
 - dtGUI::CEGUISignature, [19](#)
 - GetOrCreateOSGTexture
 - dtGUI::HUD, [40](#)
 - getOriginalHeight
 - dtGUI::CEGUITexture, [28](#)
 - getOriginalWidth
 - dtGUI::CEGUITexture, [28](#)
 - GetOSGNode
 - dtGUI::CEUIDrawable, [32](#)
 - GetOSGTexture
 - dtGUI::CEGUITexture, [29](#)
 - GetPrefix
 - dtGUI::HUD, [40](#)
 - GetProjectionNode
 - dtGUI::CEUIDrawable, [32](#)
 - getRect
 - dtGUI::CEGUIRenderer, [25](#)
 - GetRegistry
 - dtGUI::ScriptModule, [46](#)
 - GetRenderer
 - dtGUI::CEUIDrawable, [32](#), [33](#)
 - GetRootSheet
 - dtGUI::HUD, [40](#)
 - GetRootsheet
 - dtGUI::HUD, [40](#)
 - getSize
 - dtGUI::CEGUIRenderer, [25](#)

GetTextureID
 dtGUI::CEGUITexture, 29

GetTransformNode
 dtGUI::CEUIDrawable, 33

GetUI
 dtGUI::CEUIDrawable, 33

getVertScreenDPI
 dtGUI::CEGUIRenderer, 25

GetWidget
 dtGUI::HUD, 40

getWidth
 dtGUI::CEGUIRenderer, 25
 dtGUI::CEGUITexture, 29

getXScale
 dtGUI::CEGUITexture, 29

getYScale
 dtGUI::CEGUITexture, 29

guiexceptionenum.cpp, 63

guiexceptionenum.h, 64

- H -

HandleButtonClicked
 dtGUI::CEGUIMouseListener, 22

HandleButtonPressed
 dtGUI::CEGUIMouseListener, 22

HandleButtonReleased
 dtGUI::CEGUIMouseListener, 22

HandleKeyPressed
 dtGUI::CEGUIKeyboardListener, 17

HandleKeyReleased
 dtGUI::CEGUIKeyboardListener, 17

HandleKeyTyped
 dtGUI::CEGUIKeyboardListener, 17

HandleMouseDragged
 dtGUI::CEGUIMouseListener, 22

HandleMouseMove
 dtGUI::CEGUIMouseListener, 23

HandleMouseScrolled
 dtGUI::CEGUIMouseListener, 23

HandlerFunctor
 dtGUI::ScriptModule, 45

HUD
 dtGUI::HUD, 39

hud.cpp, 65

GetCEGUIPrefix, 65

hud.h, 66

- I -

IMPLEMENT_ENUM
 dtGUI, 11

inc/ Directory Reference, 7

inc/dtGUI/ Directory Reference, 6

IsFlippedHorizontal
 dtGUI::CEGUITexture, 29

isQueueingEnabled
 dtGUI::CEGUIRenderer, 25

- K -

KeyboardKeyToKeyScan
 dtGUI::CEGUIKeyboardListener, 17

- L -

loadFromFile
 dtGUI::CEGUITexture, 29

loadFromMemory

dtGUI::CEGUITexture, 29

LoadLayout
 dtGUI::HUD, 40

loadRawDataContainer
 dtGUI::ResourceProvider, 43

LoadScheme
 dtGUI::HUD, 41

- M -

m_pEventSet
 dtGUI::CEGUMemberSignatureBase, 21

m_sEventName
 dtGUI::CEGUMemberSignatureBase, 21

mainpage.h, 67

MakeCurrent
 dtGUI::HUD, 41

match
 dtGUI::CEGUMemberSignature, 19
 dtGUI::CEGUISignatureStatic, 27

mGeode
 dtGUI::CEUIDrawable, 33

mHeight
 dtGUI::CEUIDrawable, 33

mKeyboard
 dtGUI::CEUIDrawable, 33

mMouse
 dtGUI::CEUIDrawable, 33

mNode
 dtGUI::CEUIDrawable, 33

mProjection
 dtGUI::CEUIDrawable, 33

mRenderer
 dtGUI::CEUIDrawable, 33

mScriptModule
 dtGUI::CEUIDrawable, 33

mTransform
 dtGUI::CEUIDrawable, 34

mUI
 dtGUI::CEUIDrawable, 34

mWidth
 dtGUI::CEUIDrawable, 34

mWindow
 dtGUI::CEUIDrawable, 34

- O -

OGLRENDERER_VBUFF_CAPACITY
 ceguirenderer.h, 56

OnMessage
 dtGUI::CEUIDrawable, 33

operator==
 dtGUI::CEGUMemberSignature, 19
 dtGUI::CEGUMemberSignatureBase, 21
 dtGUI::CEGUISignatureStatic, 27

- R -

Renderer
 dtGUI::Renderer, 42

renderer.cpp, 68

renderer.h, 69

ResizeToMinPOT
 dtGUI::CEGUITexture, 29

ResourceProvider
 dtGUI::ResourceProvider, 43

resourceprovider.cpp, 70

resourceprovider.h, 71

- S -

S_

ceguirenderer.cpp, 55

ScriptModule

dtGUI::ScriptModule, 45

scriptmodule.cpp, 72

scriptmodule.h, 73

SetAutoResizing

dtGUI::CEUIDrawable, 33

SetCamera

dtGUI::HUD, 41

setDefaultImageCodecName

dtGUI::CEGUIRenderer, 25

setDisplaySize

dtGUI::CEGUIRenderer, 25

SetFilePath

dtGUI::HUD, 41

SetFlipHorizontal

dtGUI::CEGUITexture, 29

SetGraphicsContext

dtGUI::CEGUIRenderer, 25

setImageCodec

dtGUI::CEGUIRenderer, 25

setIsMouseCursorVisible

dtGUI::HUD, 41

SetKeyboard

dtGUI::HUD, 41

SetMouse

dtGUI::HUD, 41

SetMouseCursor

dtGUI::HUD, 41

SetOSGNode

dtGUI::CEUIDrawable, 33

SetOSGTexture

dtGUI::CEGUITexture, 29

setQueueingEnabled

dtGUI::CEGUIRenderer, 25

SetRenderBinDetails

dtGUI::CEUIDrawable, 33

SetRenderingSize

dtGUI::CEUIDrawable, 33

SetWindowSize

dtGUI::CEGUIMouseListener, 23

ShutdownGUI

dtGUI::CEUIDrawable, 33

src/ Directory Reference, 8

src/dtGUI/ Directory Reference, 5

STATIC_FUNCTION

dtGUI::ScriptModule, 45

STRINGIZE

ceguirenderer.cpp, 55

- U -

UnloadAllSchemes

dtGUI::HUD, 41

UnloadScheme

dtGUI::HUD, 41

- W -

Widget

dtGUI, 11

widget.h, 74